

TECHNOLOGY THAT INCREASES PRODUCTIVITY

SKID STEER TILLER



SST SERIES

GETS MORE FOR YOUR FIELD





BISON

SKID STEER TILLER SST SERIES



The operator can know the depth at which the soil tilling.

Allows operator to choose forward or reverse tilling by only reversing hydraulic flow.

Low flow and high flow allow these tillers to fit a wide variety of skid steers.



Keep skates allows optimal state of use.

Reduces vibration and efforts.

Makes replacing tines fast and easy.

Tines are sharpened on both edges to cut into the soil while operating forward or reverse. If bidirectional tines are used primarily rotating in one direction, they can be rotated for extend their life.



Depth Indicator

Rotor can be operate forward or reverse

Different models offers a choice between low flow or high flow.

Replaceable skid shoes.

Spiral Design of rotor a screw for each tine.

Bi-directional hardened boron steel tines.

SPECIFICATIONS

		SST-165	SST-180	SST-195	SST-210
Model	in	66"	72"	78"	84"
Overall Width	in	79"	85"	91"	97"
Tilling Width		65.5	71.2	77.5	83.5
Tilling Depth	in	0-6"	0-6"	0-6"	0-6"
Overall Height	in	18"	18"	18"	18"
Number of tines		40	44	48	52
Tine rotation		Bi-Direction	Bi-Direction	Bi-Direction	Bi-Direction
Weight	lb	683	710	745	780
Drive line		2 Motors	2 Motors	2 Motors	2 Motors
Hydro Flow needed	gpm	14-23	16-28	22-41	28-45
Hydro Pressure needed (gpm)	gpm	2,500	2,500	3,000	3,500
Drive		direct	direct	direct	direct

*Tecnomec Agrícola, S.A. de C.V. reserves the right to modify the specifications whenever it deems necessary without warning.

*Some of the pictures depict equipment that is not necessarily included as part of the standard machinery.

Contact your BISON dealer and find out the many other options available.

www.bison.com.mx



Carretera a Paso Blanco Km. 2 No. 400 / Col. Vista Hermosa C.P. 20905
Jesús María, Aguascalientes, México
Tel. (449) 92-BISON / Fax. (449) 922 4767